MAIL TO:

Request for Quotation

STATE OF UTAH
DIVISION OF PURCHASING
3150 STATE OFFICE BUILDING, CAPITOL HILL
P.O. BOX 141061
SALT LAKE CITY, UTAH 84114-1061
TELEPHONE (801) 538-3026
FAX (801) 538-3882
http://www.purchasing.state.ut.us



Solicitation Number: RF3092

Due Date: 01/27/03

Date Sent: January 13, 2003

Goods and services to be purchased:

SMALL ENGINE REPAIR TOOLS

Please complete

Company Name		Federal 1	Γax Identification Number
Ordering Address	City	State	Zip Code
Remittance Address (if different from ordering address)	City	State	Zip Code
Type ☐ Corporation ☐ Partnership Proprietorship Government	Company Contact Person	I	
Telephone Number (include area code)	Fax Number (include area cod	de)	
Company's Internet Web Address	Email Address		
Discount Terms (for bid purposes, bid discounts less than 30 days will not be considered)	Days Required for Delivery Aff required minimums)	ter Receipt o	of Order (see attached for any
The following documents are included in this solicitation: Solicit specifications. Please review all documents carefully before co		nd gener	al provisions, and
The undersigned certifies that the goods or services offered are Utah. Yes No If no, enter where produced, etc			-
Offeror's Authorized Representative's Signature	Date		
Type or Print Name	Position or Title		

STATE OF UTAH DIVISION OF PURCHASING & GENERAL SERVICES

Request for Quotation

Solicitation Number: RF3092

Due Date: 01/27/03

Vendor Name:

Item#	Qty	Unit	Description	Unit Price	Extension
001	1	LOT	SMALL ENGINE REPAIR TOOLS AS PER ATTACHED LIST AND SPECIFICATIONS.	\$	\$

WITH QUESTIONS REGARDING THE SPECIFICATIONS PLEASE CONTACT JANICE CHRISTENSEN AT (801)538-7623.

QUESTIONS REGARDING THE BID PROCESS SHOULD BE DIRECTED TO ROSEMARY FRENCHWOOD AT (801)538-3147.

REFERENCE RX#: 400 33-13

Ship To: 2091 MURPHY LANE MOAB UT 84532

FREIGHT CHARGES (if applicable)

SHIPPING POINT AND ZIP CODE				
SHIPPING WEIGHT				
MODE OF TRANSPORTATION	(Please check one)			
Q Small package/Ground	D LTL(Less than truck load) NMFC Class # NMFC Item #	Q Truckload Q -	Air	Q Other (Please specify)
TOTAL PRICE LESS FREIGHT (F	OB Origin)			\$
TOTAL PRICE INCLUDING FREIO	GHT (FOB Destination)			\$

REQUEST FOR QUOTATION - INSTRUCTIONS AND GENERAL PROVISIONS

- 1. QUOTATION PREPARATION: (a) All prices and notations must be in ink or typewritten. (b) Price each item separately. Unit price shall be shown and a total price shall be entered for each item bid. Errors may be crossed out and corrections printed in ink or typewritten adjacent and must be initialed in ink by person signing quotation. (c) Unit price will govern, if there is an error in the extension. (d) Delivery time is critical and must be adhered to as specified. (e) Wherever in this document an item is defined by using a trade name of a manufacturer and/or model number, it is intended that the words, "or equivalent" apply. "Or equivalent" means any other brand that is equal in use, quality, economy and performance to the brand listed as determined by the Division of Purchasing & General Services (DIVISION). If the vendor lists a trade name and/or catalog number in the bid, the DIVISION will assume the item meets the specifications unless the quote clearly states it is an alternate, and describes specifically how it differs from the item specified. All quotes must include complete manufacturer's descriptive literature if quoting an equivalent product. (f) By signing the quotation the vendor certifies that all of the information provided is accurate, that they are willing and able to furnish the item(s) specified, and that prices quoted are correct. (g) This quote may not be withdrawn for a period of 60 days from quote due date. (h) Incomplete quotes may be rejected.
- 2. SUBMITTING THE QUOTATION: (a) The quote must be signed in ink and returned to the DIVISION OF PURCHASING, 3150 State Office Building, Capitol Hill, Salt Lake City, UT 84114-1061 by due date and time. The "Solicitation Number" and "Due Date" must appear on the outside of the envelope. (b) The state reserves the right to consider faxed quotes. Fax quotes are submitted at the sole option and risk of the vendor and must be responsive to all conditions and specifications included in the Request for Quotation (RFQ). Access to state facsimile machine is on a "first come first served" basis and the state does not guarantee the vendor's access to the machine at any particular time. (c) All prices quoted must be both F.O.B. Origin and F.O.B. Destination. Additional charges including but not limited to delivery, drayage, express, parcel post, packing, cartage, insurance, license fees, permits, costs of bonds, or for any other purpose must be included in the quotation for consideration and approval by the DIVISION. Upon award of the contract, the shipping terms will be F.O.B. Destination, Freight Prepaid with freight charges to be added to the invoice unless otherwise specified by the DIVISION.
- 3. FAILURE TO RESPOND: Failure to respond may result in the removal of your firm from the vendor's list for the commodity(s) listed.
- **4. PROPRIETARY INFORMATION:** Suppliers are required to mark any specific information contained in their quote which is not to be disclosed to the public or used for purposes other than the evaluation of the quote. Each request for non-disclosure must be accompanied by a specific justification explaining why the information is to be protected. Pricing and service elements of any quote will not be considered proprietary. All material becomes the property of the state and may be returned only at the state's option. Quotes submitted may be reviewed and evaluated by any persons at the discretion of the state. **5. BONDS:** The state has the right to require a bid bond, payment bond and/or a faithful performance bond from the vendor in an amount not to exceed the amount of the contract
- **6. SAMPLES:** Samples of item(s) specified in the RFQ, when required by DIVISION, must be furnished free of charge to DIVISION. Any items not destroyed by tests may, upon request made at the time the sample is furnished, be returned at the vendor's expense.

7. WARRANTY (including Year 2000):

The contractor agrees to warrant and assume responsibility for each hardware, firmware, and/or software product (hereafter called the product) that it licenses, or sells, to the State of Utah under this contract. The contractor acknowledges that the Uniform Commercial Code applies to this contract. In general, the contractor warrants that: (a) the product will do what the salesperson said it would do, (b) the product will live up to all specific claims that the manufacturer makes in their advertisements, (c) the product will be suitable for the ordinary purposes for which such product is used, (d) the product will be suitable for any <u>special purposes</u> that the State has relied on the contractor's skill or judgement to consider when it advised the State about the product, **especially to ensure year 2000 compatibility and fitness**, (e) the product has been properly designed and manufactured, and (f) the product is free of significant defects or unusual problems about which the State has not been warned. In general, "year 2000 compatibility and fitness" means: (1) the product warranted by the contractor will not cease to perform before, during, or after the calendar year 2000, (2) the product will not produce abnormal, invalid, and/or incorrect results before, during, or after the calendar year 2000, (3) will include, but not be limited to, date data century recognition, calculations that accommodate same century and multi-century formats, date data values that reflect century, and (4) accurately process date data (including, but not limited to, calculating, comparing, and sequencing) from, into, and between the twentieth and twenty-first centuries, including leap year calculations. If problems arise, the contractor will repair or replace (at no charge to the State) the product whose noncompliance is discovered and made known to the contractor in writing. If there is a Year 2000 problem, the contractor agrees to immediately assign senior engineering staff to work continuously until the product problem is correcte

- **8. DIVISION APPROVAL:** Purchase Orders placed, or contracts written, with the State of Utah, as a result of this RFQ, will not be legally binding without the appropriate signature of the DIVISION.
- 9. AWARD OF CONTRACT: (a) This is an informal quotation which will not be read at a public opening; however, the information may be publicly reviewed after award. To obtain a copy of this record (tabulation) you may either enclose a stamped self-addressed envelope, or review tabulation in our office. (b) The contract will be awarded with reasonable promptness, by written notice to the lowest responsible vendor that meets the specifications. Consideration will to be given to the quality of the product(s) to be supplied, conformity to the specifications, the purpose for which required, delivery time required, discount terms and other criteria set forth in this request for quotation. (c) The DIVISION may accept any item or group of items, or overall low quote. (d) The DIVISION has the right to cancel this request for quotation at any time prior to the award of contract. (e) The DIVISION can reject any and all quotes or waive any informality, or technicality in any quote received, if the DIVISION believes it would serve the best interest of the State. (f) Before, or after, the award of a contract the DIVISION has the right to inspect the vendor's premises and all business records to determine the holder's ability to meet contract requirements. (g) Estimated quantities are for quoting purposes only, and not to be interpreted as a guarantee to purchase any amount. (h) Utah has a reciprocal preference law which will to be applied against vendors quoting products or services produced in states which discriminate against Utah products. For details see Section 63-56 20.5 -20.6, <u>Utah Code Annotated.</u> (i) Multiple contracts may be awarded if the State determines it would be in its best interest.
- 10. ANTI-DISCRIMINATION ACT: The vendor agrees to abide by the provisions of the Utah Anti-discrimination Act, Title 34 Chapter 35, U.C.A. 1953, as amended, and Title VI and Title VII of the Civil Rights Act of 1964 (42 USC 2000e), which prohibit discrimination against any employee or applicant for employment, or any applicant or recipient of services, on the basis of race, religion, color, or national origin; and further agrees to abide by Executive Order No. 11246, as amended, which prohibits discrimination on the basis of age, and Section 504 of the Rehabilitation Act of 1973, or the Americans with Disabilities Act of 1990, which prohibits discrimination on the basis of disabilities. Also vendor agrees to abide by Utah's Executive Order, dated March 17, 1993, which prohibits sexual harassment in the workplace. Vendor must include this provision in every subcontract or purchase order relating to purchases by the State of Utah to insure that the subcontractors and vendors are bound by this provision.

 11. DEBARMENT: The CONTRACTOR certifies that neither it nor its principals are presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction (contract) by any governmental department or agency. If the CONTRACTOR cannot certify this statement, attach a written explanation for review by the STATE.
- 12. GOVERNING LAWS AND REGULATIONS: All state purchases are subject to the Utah Procurement Code, Title 63 Chapter 56 U.C.A. 1953, as amended, and the Procurement Regulations as adopted by the Utah State Procurement Policy Board. These are available on the Internet at www.purchasing.state.ut.us. (Revision April 1, 1999 RFQ.Instructions)

TOOL SPECS & PRICES				
Line	ITEM	DESCRIPTION	PRICE	
1	3 in 1 Air Ratchet	Multi-Ratchet 3 in 1 Wrench Kit 5/8", shank opening		
		accepts included 1/4" hex bit holder, 3/8" sq drive retainer,		
		1/2" sq drive retainer and 3/8" universal swivel. Tool is		
		either a 3/8" or a 1/2" socket drive or a 1/4" hex bit holder.		
		2 slotted bits; #5, #7 and 2 Phillips bits; #2 #3 also		
		included. 10" long, 150 rpm, 45 ft lbs Max torque, 1/4" air		
		inlet 3/8" house size. 90 PSI max op pressure. Blow-		
		molded case.		
2	Impact Wrench	Handle Exhaust Impact Wrench, standard bolt size 1/2",		
-	impact vironon	length 7 1/2" avg. air comsump (CFM,) 4.8 airl inlet NPT		
		1/4", min. hose size 3/8", Wkg Torque ft/lb 50/400 Max		
		Torque ft/lb 450, wt lbs 4.5		
2	Hammer Kit	Pneumatic Hammer Kit, includes hammer, shank opening		
3	riailillei Kit	·		
		is 401,4 chisels (cold chisel, punch, edging and rivet cutter), piston stroke 31/2 blow per min. 2100, Air		
		, , ,		
	Tarana Masa ah 2011 05 050 la lla	consumption 4.5 and plastic case.		
4	Torque Wrench, 38", 25-250 In lbs.	Microtorque Wrenches. To use, simple turn handle to set		
		torque, twist ring to lock/unlock setting. Micrometer-style		
		scale. Torque accurate to +/-4% clockwise, +/-6%		
		counterclock-wise. Comfortable textured plastsic handles.		
		Square drive 3/8" measures 25-250 in lbs., increment 1		
		lbs, weight 1.7 lbs.		
5	Welding/Cutting Outfit, Heavy Duty	Heavy Duty Deluxe Oxygen-Acetylene Welding & Cutting		
		Outfit. Capable of welding up to 1" and cutting up to 6"		
		with optional tips. Outfit includes torch handle, w/tip mixer		
		and reverse check valves; cutting attachment and #1		
		cutting tip, #3, 5 & 7 welding tips and #1 heating assembly,		
		3' 16" by 20 twin hose; shade 5 goggles, striker; project		
		book and instruction manual. The large single stange		
		oxygen and acetylene regulators have 2, 1' 2" gauges and		
		fine turned adjusting knob.		
- 6	Grinder, Rotary	1/4 HP Industrial Rotary Grinder. No-load speed of 26,500		
"	Gillider, Rolary	RPM. Collet type chuck grips 1/8" and 1/4" diam. Shanks.		
		Trivi. Collectype chuck grips 1/6 and 1/4 diam. Shanks.		
7	Grinding Point Set, 6 Pcs.	6 Piece Grinding Point Set. Includes:		
'	Ginding Funit Set, 6 FCS.			
		Diameter Length 1" 1"		
		·		
		·		
		1/2" 1 1/2" 3/8 ' 1"		
		3 1/4" 1 1/8"		
<u></u>	Dially Profes	3 1/4" 1		
8	Dial Indicator	General Indicator with 2 1/2" Rotating Dial reads 0-100 by		
		.00 in I inch travel revolution accumulations counter. 2-		
		way readings. Lug back attachment. Meets AGD specs		

		Ta	1
9	Holder 90# Indicator	General 90-lb indicator holder adjust; within .0005 in. No	
		residual magnetism to attach small chips, filings. Holds all	
		types of indicators to AGD specs. Fine, multiple	
		adjustment for any angle. Positive on/off with authomatic	
		shutoff. Indicator holder has precision-ground steel base.	
		2" x 3 1/2" x 3 1/4" high.	
10	Screw Extractor Set, 10 pcs	10 pc Screw Extractor and Drill set. Consists of 5 screw	
	, , ,	extractors and 5 drill bits. (#1 thru 5, bits 5/64", 7/64", 1/4"	
		and 17/64") to remove broken screws, bolts. Bits provide	
		correct size to use with each screw extractor.	
11	Stud Remover, 5'16" x 3/4"	Stud Remover has 5/16" to 3/4" capacity.	
	Hammer, Sledge, Brass 1.5#	Brass Hammer. Surface protective, non-marring brass	
	3, 2, 2, 3, 3, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2,	head. 12" handle.	
13	Extension Bar Set, 3 pcs 1/2 drive	3 PC Extension Bar Set, includes 3", 6" and 10" Extension	
		bars.	
14	3 PC Wbbl Extnsn Set	Allen 3-PC 3/8" Drive Wobble Extension Set. Includes 1	
'		1/2",3", 6" lengths.	
15	Compressor, Vertical, Portable	6-OHP, 30 gallon vertical compressor. Deliveries 8.6	
	,,,	SCFM @ 40 PSI and 6.4 SCFM @ 90 PSI. 135 PSI	
		maximun working pressure. Compressor has no belts to	
		adjust and requires no oil for maintenance-free operation.	
		Handle and wheels for convenient portability. Motor	
		operates on standard 120 Volt current. Measures approx.	
		24" Long x 24" Wide x 52" High.	
		24 Long X 24 Wide X 52 Tilgii.	
16	Blow Gun Kit	Pro-Type Blow Gun Kit. Includes blow gun plus 2 piece tip	
16	Blow Gun Kit	Pro-Type Blow Gun Kit. Includes blow gun plus 2 piece tip set: 1 high flow rubber tip (fixed inch extention). 1 standard	
16	Blow Gun Kit	set; 1 high flow rubber tip (fixed inch extention), 1 standard	
		set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel.	
	Blow Gun Kit Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is	
		set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard.	
17		set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit.	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with	
17	Mini Heavy Duty Regulator	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack.	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range Spoolgun Rated @150 amps, 20 ft	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle.	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle. 20ft cable assembly. Specifically designed to be used with	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range Spoolgun Rated @150 amps, 20 ft cable	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle.	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range Spoolgun Rated @150 amps, 20 ft	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle. 20ft cable assembly. Specifically designed to be used with Professional 210 amp welder only.	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range Spoolgun Rated @150 amps, 20 ft cable	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle. 20ft cable assembly. Specifically designed to be used with Professional 210 amp welder only.	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range Spoolgun Rated @150 amps, 20 ft cable	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle. 20ft cable assembly. Specifically designed to be used with Professional 210 amp welder only. Airforce 250 A 115 V Plasma Cutter. Built in piston driven air compressor. Diagnostic light for troubleshooting.	
17	Mini Heavy Duty Regulator Welder, 210 amp, Range Spoolgun Rated @150 amps, 20 ft cable	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle. 20ft cable assembly. Specifically designed to be used with Professional 210 amp welder only. Airforce 250 A 115 V Plasma Cutter. Built in piston driven air compressor. Diagnostic light for troubleshooting. Includes ICE-12C torch with 20 ft lead, 15 ft cable with	
17 18 19	Mini Heavy Duty Regulator Welder, 210 amp, Range Spoolgun Rated @150 amps, 20 ft cable	set; 1 high flow rubber tip (fixed inch extention), 1 standard nozel. Regulator has 1/8" NPT gauge ports. Operationg range is pressures for 250 PSI at a temperature of 120 F 0 to 125 PSI relieving model standard. Professional 210 amp Welder. Delivers 210 amps of power. Single phase output range of 30-210 amps and 60% duty cycle @150 amps, 30% duty cycle @210 amps Cast Aluminum drive system. 24 V AC gun trigger circuit. Wire sizes: solid and stainless steel, .023"035", Flux cord, .030"045", aluminum, .030". Includes power cord with plug, 10 feet M15, 150 amp MIG gun and cable assembly. 10 foor work cable with clap, gas solenoid valve, flow gauge and 5 ft gas hose for use with cO2/Argon cylinder, extra contact tips, factory installed running gear and large cylinder rack. Optional Spoolgun. Rated @ 150 amps, 60% duty cycle. 20ft cable assembly. Specifically designed to be used with Professional 210 amp welder only. Airforce 250 A 115 V Plasma Cutter. Built in piston driven air compressor. Diagnostic light for troubleshooting.	

22	Glaze Breaker	Cylinder Surfacing Hone. Works with 1/4" or 3/8" electric	
~~	Glaze Breaker	drill. Has a range of 2" to 7", includes 3 - 220 grit stones.	
		The difference of 2 to 7, includes of 225 gift stories.	
23	Cylinder Hone Set.	Has 2 - 5" 180, 80 grit stones and 2 wipers. Gas engine,	
	Symmatri Herre Con	3" to 4 1/4" size range. Universal joint action. Shank,	
		extension fit 1/2" drill or drill press.	
24	Groove Cutter	Piston Rig Groove Cutter and Cleaner. Effectively	
~	Groove Guiter	removes carbon on pistons from 2" to 5" (51mm to	
		127mm) covers all major piston ring grooves, SAE and	
		metric.	
25	Mask, Flexible	Impact Goggle. Professional quality, adjustable headband	
23	IVIASK, I IEXIDIE	and tight fitting facial seal provide added safety. Fits over	
		personal glasses. Direct vent system for reduced lens	
		I'	
		fogging. Soft, flexible vinyl frame is light weight and	
		comfortable. Meets ANSI Z87.1-1989 and complies with	
		OSHA requirements for industrial eye protection.	
26	Spark Tostor	Ignition Spark Tostor	
	Spark Tester	Ignition Spark Tester.	
21	Thread Chaser	KD 14 mm and 18mm Spark Plug Opening Thread	
		Chaser. Cleans and restores 14mm and 18mm spark	
- 00	Dilet Deering Dulle:	plugs threads. Drive with 13/16" socket.	
28	Pilot Bearing Puller	OTC Pilot Bearing Puller. 3/4" reach, ID spread from 1/2"	
20	Work Darah 42 Drawar 22 2 as ft	to 1 1/2".	
29	Work Bench, 12 Drawer, 22.2 sq ft.	12 Drawer Work Bench (all metal). Has 11,608 cu inch of	
		storage. 54" W x 20" D x 1 1/2 H work surface with	
		rounded corners and banded edges. All drawers are 16	
		7/8" W x 15 3/4" D, 4 drawers are 2 1/8" H, 8 drawers are	
		4 3/8" H. No lock. Measures 54 W x 2 1/4" D x 34 H	
	West Devel 7 Devel 2 Office	overall.	
30	Work Bench 7 Drawers, 2 Ctns.	7 Drawer Work Bench. Provides 16,779 cu in of storage,	
		the extra wide 72" W x 30" D top has rounded corners and	
		banded edges. Steel base with 2 supporting center legs,	
		has leveling feet to adjust height and add stability. All	
		drawers are 16 7/8" W x 15 3/4" D; 2 drawers are 2 1/8" H,	
		4 are 4 3/8" H; 1 is 9" H. Open center provides additional	
		storage. Shelf area has steel back panel. Lockable steel	
		with 2 keys. Measures 72" W 30" D x 34" H overall.	
04	Croudoot Cot 40 mas Matria	10 Diogo Matrio Croude et Mreneh Cet la stude et 40eur	
31	Crowfoot Set, 10 pcs Metric	10 Piece Metric Crowfoot Wrench Set Includes: 10mm,	
		11mm, 12mm, 13mm, 14mm, 15mm, 16mm, 17mm,	
	Crowfoot Cot 40 Ct 1	18mm, 19mm	
32	Crowfoot Set, 10 pcs Std	10 Piece Standard Crowfoot Wrench Set Includes: 3/8",	
		7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 1".	
- 00	244 Do Tool Cot	(244 Do Mochoniolo Tool Cottin Ctondond and Matric	
33	241 Pc Tool Set	(241 Pc Mechanic's Tool Set in Standard and Metric	
		Sizes)	
		146 Sockets	
		1/4" Drive Socket: 11, Six-Point Standard Sockets; 5/32",	
		3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8", 7/16", 1/2",	
		9/16".	
		12, Six-Point Metric Sockets; 4mm, 5mm, 5.5mm, 6mm,	
		7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13,mm 14mm	

		10, Twelve-Point Standard Sockets; 3/16", 7/32", 1/4",	
		9/32", 5/16", 11/32", 3/8", 7/16", 1/2", 9/16".	
		10, Six-Point Standard Deep Sockets; 3/16", 7/32", 1/4",	
		9/32", 5/16", 11/32", 3/8", 7/16", 1/2", 9/16".	
		11, Six-Point Metric Deep Sockets; 4mm, 5mm, 6mm,	
		7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13mm, 14mm".	
		1/4" Drive Tools: QR Ratchet, 3" Extension Bar, 6"	
		Extension Bar	
		3/8" Drive Socket: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8",	
		11/16", 3/8", 13/16", 7/8"	
		17, Six Point Metric Sockets: 6mm, 7mm, 8mm, 9mm,	
		10mm, 11mm, 12mm, 13mm, 14mm, 15mm, 16mm,	
		17mm, 18mm, 19mm, 20mm, 21mm, 22mm	
		11, Twelve Point Standard Sockets: 1/4", 5/16", 3/8",	
		7/16", 1/2", 9/16", 5/8", 11/16", 3/8", 13/16", 7/8"	
		15, Twelve Point Metric Sockets: 6mm, 7mm, 8mm,	
		9mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm,	
		16mm, 17mm, 18mm, 19mm, 21mm	
		7, Six Point Standard Deep Sockets: 3/8", 7/16", 1/2",	
		9/16", 5/8", 11/16", 3/4"	
		7, Six Point Metric Deep Sockets: 13mm, 14mm, 15mm,	
		16mm, 17mm, 18mm, 19mm	
		1, Six Point Spark Plug Socket: 5/8"	
		3/8" Drive Tools: QR Ratchet, 3" Extension Bar, 6"	
		Extention Bar	
		1/2" Drive Sockets, 10, Twelve Point Standard Sockets:	
		5/8", 11/16", 3/4", 1", 11/16", 13/16", 7/8", 5/16", 1 1/8", 1	
		1/4"	
		13, Twelve Point Metric Sockets: 15mm, 16mm, 17mm,	
		18mm, 19mm, 20mm, 21mm, 22mm, 23mm, 24mm,	
		25mm, 26mm, 27mm	
		1/2" Drive Tools: QR Ratchet, 3" Extension Bar	
		12 Standard Combination Wrenches	
		1/4", 5/16", 11/32", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16",	
		3/4", 13/16", 7/8"	
		14, Metric Combination Wrenches: 6mm, 7mm, 8mm,	
		9mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm,	
		16mm, 17mm, 18mm, 19mm	
		Standard Nutdrivers	
		3/16", 1/4", 5/16", 11/32", 3/8"	
		Metric Nutdrivers: 5mm, 6mm, 7mm, 8mm, 9mm	
		Other Tools	
		20 Pc Standard Hex Key Set, 20 Pc Metric Hex Key Set,	
		Magnetic Handle, 10 Pc Screwdriver Bit Set	
		Complete 241 Pc Tool Set	
34 14	Vrench Set, 14 Pc	12 Point Roll Metric Combination Wrench Set with Roll/up	
34 1	WEIGH SEL, 14 FC	Pouch: 8mm, 10mm, 12mm, 13mm, 15mm, 17mm,	
		18mm, 19mm, 20mm, 22mm, 24mm, 27mm, 28mm,	
		32mm	
25 \	Vranch Cat. 6 Da Camba Matria		
J 35 V\	Vrench Set, 6 Pc Combo Metric	6 pc Large Size Metric Combination Wrench Set: 25mm,	
		26mm, 27mm, 28mm, 30mm, 32mm	

	1/2" Drive Metric Sockets. Thin wall
	construction gives access to hard to
	reach areas without loss of socket
	strength. Lead-in chamfer lets
	sockets slide over nuts easily,
	reduces wear. Radisued corners at
	top and bottom for comfortable feel
	and impact-resistance.
	same as above
	same as above
	same as above
: Includes:	l L
	l l
, 3/16", 1/4")	
8')	
ound Bastard, 10"	
• • •	
o Bio. Extra oiiii	
e Set Includes: 2	
	· ·
ass blades.	
ow Width 2 1/2"	
aw widii, 3 1/2	
la la alcianza Clica	
- I	
	-
gauge etc.). Blow-	
es 1/16" thru 1/2" in	· · · · · · · · · · · · · · · · · · ·
lastic Case.	Hex Key Set, 13 pcs, Ball End
4mm, 4.5mm,	
, 10mm long arm	
	20 Pc Pro Screwdriver Set
ck Handles,	
4"x2 1/2", 1/4"x4",	
x8", #0x3", #1x4",	
ound Bastard, 10" ard, 10" Mill , 8" Slim Taper, 10' at File, 10" Flat 6" Dlb. Extra Slim e Set. Includes: 2 or value tappets, and master feelr ass blades. aw Width, 3 1/2" le lock jaws. Slim for fast set-up. ons ombines the 58 Pc bie Set, but includes gauge etc.). Blow- es 1/16" thru 1/2" in lastic Case. 4mm, 4.5mm, , 10mm long arm ck Handles, 4"x2 1/2", 1/4"x4",	19 Piece File Set 6 Piece Piece Pry Bar Set 5 Piece Thickness Gauge Set 5" Jaw Bench 3 Jaw Puller 6" Tap & Die Set 107 Pcs. Drill Bit Set, 29 Pcs. Hex Key Set, 13 pcs, Ball End 20 Pc Pro Screwdriver Set

50	3 Pc Professional Retaining Ring	Professional Pliers Internal and External Retaining Ring Plier Kit includes: External sizes 1/4" thru 2", External sizes 3/8" thru 2", Professional Pliers w/adjustable stop. External sizes 1/8" thru 1" Internal adjustable stop. Professional Plier w/Ratchet Lock. External sizes 1 1/2" thru 4" Internal sizes 1 13/16" thur 4' w/Ratchet Lock. In heavy molder plastic case with top kits, hex wrench instructions.	
51	Micrometer	Electronic Digital Micrometer. On-line direct conversion from standard to metric. Easy to see LCD readouts. Low battery and error alarm features, uses 1 SR-44 battery included. Measures from 0-1"/0-25mm. Accurate +/00005"/001 mm. Thimble and barrel are marked for mechanical readings to .001". Features ratchet stop and lock with carbide-tipped anvil and spindle. Auto shut-off after 4 minutes of non-use.	
52	Grinder 7" Pro Ange 13 Amp 8000	Rated Grinders size 7", amps 13.0, rpm 6,000 includes grinding wheel, wrench guard.	
53	8" Grinder	Professional 8" Grinder. Cast metal base, includes 1 - 36 grit wheel and 1 - 60 grit wheel. 115 V, UP listed.	
54	Crimped Medium Face Wire Wheel	Grit course size 8"x3/4" Arbor Hole 1/2" - 5/8".	
	Grinding Wheel	Aluminum-Oxide Grinding Wheels, 24 grit, fits 5/8" x 11 spindle 7" D	
56	7" x 5/8'" Spindle Kit		
	Drill Press	12" Bench Top Drill Press, all cast iron. 2/3 hp, work table; tilt 45 degrees, ranges 7/64"x5/8", 12" travel.	
58	Vise, 3" Cross Trvl, 7" Longitudinal	Drill Press w/Vices. Size 3", Jaw width 3", Jaw openings 3", throat depth 1".	
		Grand Total	